

GPS 126 & 128



Internal or Remote, that is the Question

With its large, high contrast, 4.25" LCD display and a powerful 12 parallel channel receiver the GPS 126 and 128 are the ideal choice for the navigator who wants more than a handheld—without the cost, complexity and large footprint found in typical fixed mount units.

The built-in GPS antenna makes the GPS 126 perfect for the mariner that navigates from an open console, the GPS 128 with its remote mount antenna is the choice for the enclosed bridge or cabin.

The GPS 126 and 128 marine navigators feature a customized moving map display with user-selectable waypoint symbols and comments, dedicated zoom keys help to make operation straight forward and intuitive. User-selectable highway or compass navigation pages provide graphic steering guidance to your destination, eliminating the guesswork when you're trying to find your favorite hotspot.

These powerful features combined with GARMIN's user friendly operating system make the answer easy.

- 12 parallel channel receiver tracks and uses up to 12 satellites for fast acquisition and a tight lock on satellites.

- Large, backlit LCD display with easy-to-read characters, moving map plotting, and dedicated zoom keys for straight forward, intuitive operation.

- User-selectable waypoint symbols and comments enhance map display information.

- Proximity waypoint feature warns you of approaching hazardous areas.

- Internal GPS antenna, perfect for the open top installation (GPS 126).

- Differential-Ready accuracy — just add the optional GBR 21 receiver for accuracy to 1-5 meters, regardless of Selective Availability.

- 500 waypoints, 20 routes of up to 30 waypoints, anchor, arrival and CDI alarms, one touch MOB and GOTO functions.



GPS 126 & 128

Navigation Features

| | |
|--------------|--|
| Waypoints: | |
| Total: | 500 |
| Nearest: | 9 (automatic) |
| Proximity: | 9 |
| Routes: | 20 reversible routes with up to 30 points each, plus MOB and TracBack™ modes |
| TracBack™: | Automatic track log navigation |
| Track Log: | 1024 points |
| Map Datums: | 107 including one User Datum |
| Coordinates: | Lat/Lon, UTM/UPS, MGRS, plus 7 grids, including Maidenhead and User UTM |

Performance

| | |
|--------------------|---|
| Receiver: | Differential-ready 12 parallel channel receiver continuously tracks and uses up to twelve satellites to compute and update position |
| Acquisition Times: | |
| Warm: | Approx. 15 seconds |
| Cold: | Approx. 45 seconds |
| AutoLocate™: | Approx. 5 minutes |
| EZinit: | Easy initialization, 45 seconds |
| Update Rate: | 1/second, continuous |
| Accuracy: | |
| Position: | 15 meters (49 feet) RMS* 1-5 meters (3-15 feet) RMS with GARMIN GBR 21 DGPS receiver (optional) |
| Velocity: | 0.1 knot RMS steady state |
| Dynamics: | 3g's |
| Interfaces: | NMEA 0183 and RTCM 104 DGPS corrections |
| Antenna: | |
| GPS 126: | Internal QuadHelix |
| GPS 128: | Remote Marine Mount with 30' of cable |

Power

| | |
|---------|-----------|
| Source: | 10-40 vDC |
| Usage: | 2 watts |

Physical

| | |
|----------------|--|
| Size: | 4.9"H x 5.3"W x 2.4"D (12.45 x 13.36 x 6.1 cm) |
| Weight: | Less than 1 lb. (454g) |
| Display: | 4.25" diagonal (10.8 cm) high-contrast LCD with three-level backlighting |
| Case**: | Full gasketed, high impact plastic alloy |
| Temp. Range: | 5°F to 158°F (-15°C to 70°C) |
| Memory Backup: | Internal lithium battery |

Accessories

| | |
|-----------|---|
| Standard: | GPS 126/128 receiver Power/Data cable Owner's Manual Surface Mount Bracket Quick Reference Guide GA 28 Antenna (GPS128 only) |
| Optional: | A/C Adapter Cigarette Lighter Adapter PC Kit |

Specifications are preliminary and subject to change without notice.

* Subject to accuracy degradation to 100m 2DRMS under the United States Department of Defense imposed Selective Availability Program.

** Meets IEC (European Community Specification) 529 IPX7 for protection against immersion for 30 minutes at a depth of 1 meter.

© 1998 GARMIN Corporation



GARMIN International
1200 East 151st Street
Olathe, Kansas 66062, U.S.A.
913/397.8200 FAX 913/397.8282

GARMIN (Europe) Ltd.
Unit 5, The Quadrangle, Abbey Park Industrial Estate
Romsey, SO51 9AQ, U.K.
44/1794.519944 FAX 44/1794.519222

GARMIN (Asia) Corporation
4th Floor, No. 1, Lane 45, Pao-Hsing Road
Hsin-Tien, Taiwan
886/2.917.3773 FAX 886/2.917.1758

www.garmin.com